

swingo[®] 1255 B

Battery powered automatic scrubber drier for floor cleaning

TASKI swingo 1255 B brings you:

- The ideal size for best performance
- Excellent cleaning and drying results
- Simple to use and easy maintenance
- Durability and robustness

Ideal size for best performance

The patented IntelliFlow-system always ensures the right amount of cleaning solution on the floor and leads to significant water savings. This, in combination with the 60 L tank volume, increases productivity and cuts the number of time consuming tank filling stops during the cleaning operation. The dual-axle system ensures easy handling and allows comfortable use of the machine.

Excellent cleaning and drying results

The patented brush design follows the floor profile and delivers nearly even pressure allocation along the full working width. The 2 brushes with offset to side allow perfect cleaning along walls and under racks. This results in excellent soil removal and floor appearance. The patented V-shaped squeegee allows perfect water pick-up on all floor types, even on structured and grouted/tiled floors. Special squeegee blades and a direct suction line allow pick-up of small debris (e.g. cigarette butts) without clogging. Due to the proven 3-wheel concept, adjustments of the squeegee are not necessary anymore.

Simple to use and easy maintenance

All components which need frequent maintenance are colour coded in yellow and can be removed easily without tools. The dashboard is self-explanatory with minimum training needed and displays all required information. Fewer parts to maintain and easy accessibility make the machine extremely service friendly.

Durability and robustness

The use of high tech material and long life components enhance the machine's uptime while reducing service and repair costs to a minimum.



swingo® 1255 B

Description		Description	
Theoretical performance	2475 m ² /h	Dimensions (L x W x H)	142 x 58 x 117 cm
Working width	55 cm	Turning circle	1,33 m
Squeegee width	80 cm	Brush system	2 x 28 cm
Solution tank (nominal)	60 l	Brush pressure	48 kg
Recovery tank (nominal)	60 l	Cleaning Speed	4,5 km/h
Nominal consumption	1000 W	Cable length of integrated battery charger	3 m
Rated voltage	24 V	Sound level	< 70 dB(A)
Battery capacity	100-140 Ah/C5	Protection class (with BMS / without BMS)	II/III
Battery run time (nominal)	up to 3h	Approvals	CE/CB Test cert./ ÖVE/cETL
Machine weight	260 kg		

Model	Article number
TASKI® swingo® 1255 B Power	
TASKI® swingo® 1255 B Power BMS	
TASKI® swingo® 1255 B Power EBU	
TASKI® swingo® 1255 B Power BMS EBU	

Accessories	Article number
Pad drive harpoon grip 28 cm	7510634
Scrubbing brush standard 28 cm	7519395
Scrubbing brush washed concrete 28 cm	7510632
Scrubbing brush abrasive 28 cm	7510633
TASKI® IntelliDose® kit for swingo 755/855/1255	7517125
Filling hose with universal water coupling	8502830

Description of Features
BMS (Battery Management System): Integrated in the machine, the battery charger prevents deep discharging of the battery and monitors the charging process.
EBU (Electronic brush unit): brush unit is lowered automatically
WD (Wheel Drive): The variable working speed (up to 4.5km/h) and reverse speed (up to 2.5km/h) guarantees ergonomic and effortless working and increases the performance compared to non-wheel drive models.
IntelliFlow (Cleaning Solution Dosing): With the patented IntelliFlow system, exactly the right amount of cleaning solution is dosed onto the floor depending on how fast the machine is going. The slower you go (e.g. around corners) the less is dosed. The result is no puddles around corners, a significant saving in cleaning solution and significantly increased productivity of the machine.